





Model	MHSD-2700RC / MHSD-2700RCT
Screen Technology	TFT AM LCD
Active Screen Size (Diagonal)	27"
Active Screen Size (H x V)	597.6 x 336.15 mm
Aspect Ratio	16:9
Resolution	1920 x 1080
Pixel Pitch	311.25 μm
Viewing Angle (H, V)	178°
Maximum Luminance	350 cd/m ²
Contrast Ratio	3000:1
Color	16.7 Millions
Response Time (Tr + Tf)	12 ms
Video Inputs Signals	SDI / HDMI / DVI & VGA (Please Select One Option)
Interface Port	Digital Input :- SDI, HDMI Port, DVI
	Analog Input :- 15 Pin D-Sub
Video Outputs Signals	Digital :- HDMI
	Analog :- VGA
Recording System	In-Built, Fully Integrated with Monitor
	1TB Storage (Expandable to 2TB)
	Simultaneous Recording & Video Display
	Other Features :-
	Recording Start & Pause Button
	Screenshot Button
	USB for Copying Recorded Videos
	Ethernet for Connectivity with Hospital / Clinic Network
	Optional Features :-
	Wi-Fi, Bluetooth
	Output Signal for Connecting to Slave / Passive Monitor
Power Requirements (Nominal)	AC 100~240V
Power Consumption (Nominal)	90W Max
Power Saving	EPA, VESA Standard
Operating Temperature	0 to +50°C
Storage Temperature	-20 to +60°C
Relative Humidity	10% to 90% (Non Condensing)
Housing Color	White
Housing Material	Metal
Mounting Standard	VESA (100 mm)
Warranty	2 Years
Applications	Laparoscopy, GI Endoscopy, Bronchoscopy, Surgical Microscopy,
	Arthroscopy, Neuro-Spine Surgery, Digital OR
Touch Screen (Optional)	Capacitive Type Multi Point Touch Screen (USB Interface)

HIGHNESS MICROELECTRONICS PVT. LTD.



Available at:

Xavier Med Pvt. Ltd. 1-10-51/2, Road 6B, Dwarakapuram, Dilsukhnagar, Hyderabad - 500060 www.buyxavier.com

Customer Care: 8008895680 Service: 8008895079

