

# Meditec 1020

## Portable Emergency Ventilator







## **Technical Specifications**

Pneumatically Driven Ventilator	✓
Driven from pipeline or cylinder operated with an automatic switch-over valve	✓
IPPV Ventilation Mode	✓
Adult & Pediatric	✓
I:E Ratio	Preset (1:2)
Oxygen Concentration	100%
Minute Volume (Adjustable)	2–15 Ltr/min
Breathing Frequency (Adjustable), at Sea Level	8–30 bpm
Noise	<65 db
Cylinder Time - 3 Ltr. cylinder when fully charged (using MV of 6 l/m)	>60 min
Driving Gas Pressure	280-600 kPa
Dimensions (mm) W x H x D	116 x 61 x 191
Weight	1.5 Kg
Storage Temperature	0°C–50°C
Operating Temperature	0°C–50°C
Storage Atmospheric Humidity	Up to 95%
Operating Atmospheric Humidity	Up to 90%

### Standard Accessories

- Ventilator Main Unit
- High Pressure Hose
- Breathing Hose
- 2/3 Ltr. O<sub>2</sub> Cylinder
- Breathing Valve
- Face mask
- Regulator with Flowmeter & Gauge
- Cylinder Refilling Attachment
- Dust Proof Carry Bag



Dust Proof Carry Bag





Manufactured in India by

#### **Allied Medical Limited**

76-77, Udyog Vihar, Phase IV,

Gurugram - 122 015, Haryana, INDIA

Phone : +91 124 4111444

Mobile : +91 9811184252 Toll Free : 1800 102 7879

E-mail : sales@alliedmed.co.in Website : www.alliedmed.co.in

Available at:

### XAVIER MED PVT. LTd.

1-10-51/2, Road 6B, Dwarakapuram, Dilsukhnagar, Hyderabad - 500060

www.buyxavier.com

Customer Care: 8008895680, Service: 8008895079 00336R0 Ver. 20.7