



Model: 3018 SFD

ROTO 360



SPECIAL FEATURES



SS316 Grade Flow Control Mechanism



Digital Timer with inbuilt Hour Counter



Advance Thrust Design Air-Jet Nozzle

"For effective application of disinfectants, biocides, fungicides and pesticides."

In Hospitals, Labs, Pharmaceutical Industries, Clean Rooms, Healthcare, Biotech & Tissue Culture Labs, Dairies, Food Processing Areas & Hatcheries etc.

5 YRS. / 500 HRS. LIMITED WARRANTY *

Specifications	3018 (SFD)
Timer Devices	Digital Timer (1 ~ 99 Min)
Working Hours Counter	Available (Digital)
Particle Size	Uniform Sub microns
Liquid Flow Rate	1 ~ 3 Ltrs. / Hr. (Adjustable)
Flow control Mechanism	Available SS 316
Nozzle System	SS 316 grade, Air-Jet Nozzle (Advance Thrust Design)
Tank Capacity	6.5 Ltrs.
Tank MOC	SS 316 L
Noise level	< 88 db @ 1 Meter
Air Filter	Triple stage with clamp
Area Coverage	> 20,000 Cubic. Fts.
Motor Speed	24,000 RPM (Approx.)
Power Supply	230 VAC, 50/60 Hz.
Material Of Construction (MOC)	Hardware: SS 304. Strainer, Nipples: SS 316. Tubings: Silicon grade (FDA & USP CLASS VI Complient)
Dry Weight	7 ~ 8 Kgs.





Presenting the all new, Roto360 Turn Table (an accessory). A 360° Rotating Device from IFS that vastly improves the performance of Nanofog 30 series foggers.

Salient Features

- \square 360° rotation increase area coverage. almost thrice than, without it.
- Help fog spread in all direction & reach every corner of the space.
- 🛮 Ensures 'equal' distribution of the fog into the air.
- Prevent condensation of fog particles due to the movement.
- Saves time as effectively treat the area in less time.
- ☐ NIL maintenance & trouble free operation.



Available at:

XAVIER MED PVT. LTd.

1-10-51/2, Road 6B, Dwarakapuram, Dilsukhnagar, Hyderabad - 500060 www.buyxavier.com

Customer Care: 8008895680, Service: 8008895079