



Multipara PATIENT MONITOR



Model: LM-T12

Features

- 12.1 Inch. VGA + Touch Screen TFT LCD
- Suitable for Bedside, Operation room, ICU etc.
- Support various modules including 3/5/12 Leads ECG, RESP, SPO2, NIBP, IBP, CO2, AG etc
- Multi-display Large font, Standard, Full Heads, Trend, OxyCRG 720h Monitoring Data Storage.
- Built-in detachable rechargeable lithium battery (about 4h)
- Support multi-language, Central Monitoring System

ECG

- Lead Mode: I, II, III, AVT, AVL, AVF, V
- Gain x 0.25 x 0.5 x 1, x1, x2
- Heart Rate 15-300 BPM (Adult) 15-350 BPM (Neonatal)
- Respiration: 1 BPM
- Accuracy: +/- 1%
- ST measurement Range: -2.0 +2.0 mY
- Accuracy: +/- 10%
- Pacemaker: Yes
- Sweep Speed: 12.5mm's, 25mm's, 50mm's
- Band Width: Diagnostic: 0.05 - 130HZ
- Monitor: 0.5 - 40HZ
- Surgery: 1-2 HZ

SPO2

- Measure Range: 0-100%
- Resolution: 1%
- Accuracy: +/-2% (70-100%)
- Pulse Rate: 20-250 BPU
- Resolution: 1BPM
- Accuracy: 3 BPM

NIBP

- Work Mode: Manual, Automatic Continuous
- Unit: mmHg, kPu
- Resolution: 1mmHg
- Accuracy: 5mmHg Port Upgrde Via Network

RESP

- Measure Range: 0-150BrM
- Resolution: 1BrPM
- Accuracy: +/-2%

TEMP

- Measure Range: 0.50OC
- Resolution: 0.1OC
- Accuracy: +/-0.1C

Available at:

XAVIER MED PVT. LTD.

1-10-51/2, Road 6B, Dwarakapuram,
Dilsukhnagar, Hyderabad - 500060

www.buyxavier.com

Customer Care: 8008895680

Service: 8008895079