

ECG-03

Three Channel ECG



5.7" Color Screen

Touch Operation

Mass storage Device

USB & SD Memory

JPG/PDF Reports

PC Review & Print



ECG-03

Three Channel ECG

Functional Characteristics

- 12 lead ECG synchronous sampling system.
- Thermal printer with 80mm print paper, synchronization print.
- 5.7" color touch-screen, both push-button and touch operation.
- Automatic measurement, calculation, analysis, waveform freezing.
- Support USB flash disk & SD memory.
- Data transmitting to PC via RS232/USB.
- Patient's information can be input.
- Historical data can be reviewed and printed.
- Built-in rechargeable li-ion battery, AC/DC power conversion.
- Sleep mode to save energy and extend LCD life
- Portable design with hidden handle, convenient to carry.
- Lead off & lack off paper detection function.
- 7 level printing thick can be chosen.
- Adapt to 110-230V, 50/60Hz AC power supply



Product Features



Touch Mode



Quick Input



Convenient Setting



Unlimited Storage

Technical Index

CMRR	≥ 100dB, with AC Filter	Calibrating voltage	1mV± 3%
Input circuit	Floating, Protection against defibrillator effect	Voltage tolerance	± 500mV
Input circuit current	≤ 0.1μA	Time Constant	≥ 3.2s
Resolution	12bit/1000Hz	Frequent response	0.05Hz~150Hz
Operation mode	Manual/Auto	Noise level	≤ 15 μVp-p
Filter	AC, ECG Filter	Threshold	≤ 20μV
Drift filter	Anti-Drift System	Paper speed	25, 50mm/s (± 3%)
Input impedance	> 50MΩ	Sensitivity	5, 10, 20mm/mV
Patient current leakage	< 10μA	Recorder	High resolution thermal printer
Specification of fuse	T1.6A 250V Ø5×20	Battery	Li-ion Battery(11.1V,3800mAh)
Recording paper	Thermal recording paper	Dimension	360mm×250mm×68mm

Available at:

XAVIER Med Pvt. Ltd.

1-10-51/2, Road 6B, Dwarakapuram, Dilsukhnagar, Hyderabad - 500060

www.buyxavier.com

Customer Care: 8008895680, Service: 8008895079