

MedLight 40 + 40



Minor Procedure Illumination Light

Once activated, lights at the center pod remain illuminated.



Integrated Video System (Optional)

The MedLight LED lights are available with a fully integrated, high quality Samsung make camera system. The optional camera can be suspended on separate arm.



Endo Light
MedLight series offer an
Endo Light setting.

MedLight — S E R I E S

The Next Level of LED Surgical Lights

An ISO 9001:2015, ISO13485:2016 & **C €** Certified Co.



Technical Specifications

MedLight 40+40

ght Head Size	625 mm
ght Intensity @ 1 m	350,000 Lux
ocus Size	15-30 cm
ocus Control Adjustment	Automatic
epth of Illumination	140 cm
olor Temperature	3700K,4300K,4800K
ariable Color Temperature	3500K-5000K
olor Rendering Index Ra (1)	96
olor Rendering Index R9 (red) (2)	≥ 90
umination Range	10%-100%
ndoscopy Setting	5%
umber of LEDs	86
fe-Span of LEDs	60000 hrs
ower Consumption	64 W
ontrol Unit	SMPS



Smart Sensor Technology

A system of Sensor in the light decreases the illumination of the LEDs directly above the surgeon head and increase the illumination on the surgical field.



Aerodynamics and Laminar Compatibility

Dome design with low aerodynamic resistance protects the surgical room's laminar air flow during the operation.

Dome is made of high quality fire resistant ABS material.

Camera with DVR (Samsung make)

Video System	High Definition 720p/1080i
Size	1/2.8"
Effective Number of Pixels	1952 (H) x 1116 (V)
Resolution	16:9 Full HD (1080p) Resolution Support
S/N Ratio	50dB
Optics	32x Optical Zoom
	16x Digital Zoom
	Auto Focus
Focal Length (mm)	4.44~142.6mm (Optical 32x)
Min. Illumination	0.15 Lux@F1.6 (Color)
	0.015 Lux@F1.6 (B/W)
Minimum Working Distance	1.5m
DVR Recording Capacity	1TB / 250 hrs
Power Consumption	4.2W
Power Source	12V DC/24V AC



Available at:

Xavier Med Pvt. Ltd.

1-10-51/2, Road 6B, Dwarakapuram, Dilsukhnagar, Hyderabad - 500060 www.buyxavier.com

Customer Care: 8008895680, Service: 8008895079