



















360° ROTO

Model: FOGG-PRO (SSF)



"For effective application of disinfectants, biocides, fungicides and pesticides."

in Hospitals, Labs, Pharmaceutical Industries, Clean Rooms, Healthcare, Biotech & Tissue Culture Labs, Dairies, Food Processing Areas & Hatcheries etc.







Digito Meter



Flow Control Mechanism



Advance Nozzle



Air Filter



Chemical Filling Space

Technical Specification Table

Technical Specification	FOGG-PRO (PLF)	FOGG-PRO (SSF)	FOGG-PRO (PL)	FOGG-PRO (SS)
Timer Devices	Digital Timer (1 to 99 Min)			
Delayed Time	Delayed start to leave the premises & Auto OFF operations.			
Working Hours Counter	Available (Digital)			
Paricle Size	Uniform Sub-Microns			
Liquid Flow Rate	1 ~ 3 Ltrs. / Hr. (Adjustable)		1 ~ 3 Ltrs / Hr (Fixed)	
Flow Control Mechanism	Available SS 316		Not Available	
Nozzle System	SS 316 Grade , Air-Jet Nozzle (Advance Thrust Design)			
Tank Capacity	8 Ltrs.	5 Ltrs.	8 Ltrs.	5 Ltrs.
Tank MOC	HDPE	SS 316 L	HDPE	SS 316 L
Noise Level	< 88 db @ 1 Meter			
Air Filter	Triple Stage with clamp			
Area Converge	>20,000 Cubic. Fts.			
Motor Speed	24,000 RPM (Approx.)			
Power Supply	230 VAC , 50/60 Hz.			
Material of Construcion (MOC)	Hardware: SS 304. Strainer, Nipple: SS 316. Tubings: Silicon grade (FDA & USP CLASS VI Compliant)			
Dry Weight	7 ~ 8 Kgs.			



360° ROTO

Presenting the all new, Roto-Table (An Accessory). A 360° Rotating Device from J & S Enterprises that vastly improves the performance of FOGG-PRO fogger

SALIENT FEATURES

- ◆ 360 rotation increase area coverage. Almost thrice than, without it.
- ◆ Help fog spread in all direction & reach every corner of the space.
- Ensures 'equal' distribution of the fog into the air.
- Prevent Condensation of fog particles due to the movement.
- Saves time as effectively treat the area in less time.
- NIL maintenance & trouble free operation.

